

# Fittings

**700 bar**

Power Team fittings:  
All applications.



9670

HYDRAULIC ACCESSORIES

	<b>9190</b>	Hyd. tubing. 3/8" O.D. x .065" wall, 15,3 m. (10 pieces 1,53 m long.) Wt. 5,5 kg.
	<b>9670</b>	Tee adapter. For installing gauge between pump and hose coupling. Has 1/4" and 3/8" NPTF female and 3/8" NPTF male ports. Wt. 0,2 kg.
	<b>9671</b>	Double tee adapter. Permits use of more than one cylinder in series with one pump. Three 3/8" NPTF female ports. Wt. 0,5 kg.
	<b>9672</b>	Service tee. Two 3/8" NPTF female internal, one 3/8" NPTF male external. Wt. 0,3 kg.
	<b>9673*</b>	Swivel connector. 3/8" NPSM male, 1/4" NPSM female. Wt. 0,1 kg.
	<b>9674</b>	Male connector. 43 mm long, 1/4" x 3/8" NPTF. Wt. 0,1 kg.
	<b>9675*</b>	Swivel connector. 3/8" NPTF male, 3/8" NPSM female. Wt. 0,1 kg.
	<b>9676*</b>	Swivel connector. 1/4" NPTF male, 3/8" NPSM female. Wt. 0,1 kg.
	<b>9677*</b>	45° swivel connector. 3/8" NPTF male, 3/8" NPSM female. Wt. 0,1 kg.
	<b>9678</b>	45° fitting. Used when mounting gauge at an angle on connection such as 9670. Male and female 1/4" NPTF ends. Wt. 0,1 kg.
	<b>9679</b>	Connector. 1/4" NPTF female and 3/8" NPTF male. Wt. 0,1 kg.
	<b>9680</b>	Coupling. Both ends 3/8" NPTF female. Wt. 0,1 kg.
	<b>9681</b>	Street elbow. Male and female 3/8" NPTF ends. Wt. 0,1 kg.
	<b>9682</b>	Male connector. 43 mm long, 3/8" NPTF male ends. Wt. 0,1 kg.
	<b>9683</b>	Male connector. 57 mm long, 3/8" NPTF male ends. Wt. 0,1 kg.

	<b>9684</b>	Male connector. 57 mm long, 1/4" NPTF male ends. Wt. 0,1 kg.
	<b>9685</b>	Coupling. 1/4" NPTF female and 3/8" NPTF female. Wt. 0,1 kg.
	<b>9686</b>	90° elbow. 3/8" NPTF female ends. Wt. 0,2 kg.
	<b>9687</b>	Pipe plug. Heat-treated, 3/8" NPTF. Wt. 0,1 kg.
	<b>9688</b>	Pipe plug. Heat-treated, 1/4" NPTF. Wt. 0,1 kg.
	<b>9689</b>	Connector. 1/4" NPTF male and 3/8" NPTF female. Wt. 0,1 kg.
	<b>9690</b>	Male connector. 43 mm long, 1/4" NPTF male ends. Wt. 0,1 kg.
	<b>9692</b>	Straight connector. 3/8" tube x 3/8" male NPTF. Wt. 0,1 kg.
	<b>9693</b>	90° elbow. 3/8" tube x 3/8" male NPTF. Wt. 0,1 kg.
	<b>9694</b>	45° elbow. 3/8" tube x 1/4" male NPTF. Wt. 0,1kg.
	<b>9695</b>	Tee. 3/8" tube. Wt. 0,1 kg.
	<b>9696</b>	Male run tee. 3/8" tube x 1/4" male NPTF. Wt. 0,1 kg.
	<b>9697</b>	Male branch tee. 3/8" tube x 1/4" male NPTF. Wt. 0,1 kg.
	<b>9698</b>	Cross. 3/8" tube. Wt. 0,2 kg.
	<b>9699</b>	45° gauge fitting. 3/8" NPTF male and female, and 1/4" NPTF female at 45°. Wt. 0,3 kg.
	<b>9705</b>	Fitting, swivel. 3/8" NPTF male to 3/8" NPTF female. 90° fitting with internal 370 micron screen. May be rotated 360° about male thread axis.

**NOTE:** Power Team hydraulic fittings are intended for use with our high pressure hydraulic products and are suitable for use at max. working pressures of 700 bar unless otherwise noted.

\* **CAUTION:** On part numbers 9673, 9675, 9676 and 9677 the female swivel end of these adapters is a straight pipe thread (NPSM) with a 30° seat. All male pipe fittings that are used with these female swivel adapters must have an internal 30° seat in order to effect a proper seal. All Power Team male fittings are manufactured with a 30° seat except 9687 and 9688.